



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

NL000596

45th  
8.0.1  
2/3/01

11002 U.S. PTO  
10/015835  
12/10/01

Bescheinigung

Certificate

Attestation

Die angehefteten Unterla-  
gen stimmen mit der  
ursprünglich eingereichten  
Fassung der auf dem näch-  
sten Blatt bezeichneten  
europäischen Patentanmel-  
dung überein.

The attached documents  
are exact copies of the  
European patent application  
described on the following  
page, as originally filed.

Les documents fixés à  
cette attestation sont  
conformes à la version  
initialement déposée de  
la demande de brevet  
européen spécifiée à la  
page suivante.

Patentanmeldung Nr. Patent application No. Demande de brevet n°

00204633.2

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

I.L.C. HATTEN-HECKMAN

DEN HAAG, DEN  
THE HAGUE, 24/08/01  
LA HAYE, LE

***This Page Blank (usp10)***



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

**Blatt 2 der Bescheinigung  
Sheet 2 of the certificate  
Page 2 de l'attestation**

Anmeldung Nr.:  
Application no.: 00204633.2  
Demande n°:

Anmeldetag:  
Date of filing: 18/12/00  
Date de dépôt:

Anmelder:  
Applicant(s):  
Demandeur(s):  
Koninklijke Philips Electronics N.V.  
5621 BA Eindhoven  
NETHERLANDS

Bezeichnung der Erfindung:  
Title of the invention:  
Titre de l'invention:  
Audio reproducing device

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s) revendiquée(s)

Staat:  
State:  
Pays:

Tag:  
Date:  
Date:

Aktenzeichen:  
File no.  
Numéro de dépôt:

Internationale Patentklassifikation:  
International Patent classification:  
Classification internationale des brevets:

/

Am Anmeldetag benannte Vertragsstaaten:  
Contracting states designated at date of filing: AT/BE/CH/CY/DE/DK/ES/FI/FR/GB/GR/IE/IT/LI/LU/MC/NL/PT/SE/TR  
Etats contractants désignés lors du dépôt:

Bemerkungen:  
Remarks:  
Remarques:

**This Page Blank (uspio)**

EPO - DG 1

15.12.2000

1

Audio reproducing device

18.12.2000

(100)

The invention relates to an audio reproducing device for reproducing an audio signal.

Nowadays an audio reproducing device sometimes has the possibility to also  
5 reproduce a multi channel audio signal comprising for example surround sound signals and/or a so-called centre signal. By also reproducing multi channel, for example surround sound signals and/or a centre signal the listener experiences this as a more natural sound.

One of the disadvantages of the known audio reproducing devices is that for  
10 example the surround sound signal is most of the times at a too low level. Further when for example the surround sound signal is increased in most of the cases the surround sound signal becomes too dominant and in some cases becomes distorted. The same disadvantages are encountered with the other parts of the multi channel audio signal except for the "normal" left and right signal part.

15 An object of the invention is to provide an audio reproducing device with possibility of amending the multi channel audio signal not having the disadvantages of the prior art devices. To this end an audio reproducing device according to the invention comprises to the features of claim 1.

20 By processing the multi channel audio signal part(s) in such a way that the function for that part has an linear slope for a signal part at low level but is an monotone decreasing slope for a audio signal part at a higher level the disadvantages of the prior art devices are overcome.

25 Experiments have shown that the multi channel audio signal reproduction is substantially improved. The speech intelligibility is improved, dialogs between persons (in the low-level part of the audio signal) and the loud sound effects become more brilliant (in the higher level part of the audio signal).

Embodiments of the invention are described in dependent claims.

The invention and additional figures, which may optionally be used to implement the invention to advantage will be apparent from and elucidated with reference to the examples as described here below and here and after and shown in the figures. Herein  
5 shows:

Figure 1 shows schematically an example of an audio-reproducing device according to the invention,

Figure 2 shows an example of enhancing means for use in an audio reproducing device according to the invention.

10 Figure 1 shows an example of an audio reproducing device 1 according to the invention. The audio reproducing device comprises an input  $I$  for receiving an audio signal, in this example  $k$  channels.

The audio input is coupled to an audio pre-processing unit PPU for pre-  
15 processing the audio input signal.

After pre-processing the audio signal in the pre-processing unit PPU, the  $k$  signal parts are supplied to an audio-processing unit APU.

In the pre-processing unit PPU for example the incoming signals can be  
20 transformed into a different number output signals to be supplied to the audio-processing unit. For example the input signals can have two signal parts and the output signals of the pre-processing unit can have 5 signal parts, the so-called transfer to surround sound signals. Further it is possible that the input signals already have 5 signal parts in case of DVD and the output also has 5 signal parts. In this way it possible to obtain the required number of input  
25 signals to be handled further in the audio-processing unit APU.

In this audio-processing unit APU the  $n$  channel output signal parts (for example  $n=5$ , as described above) are splitted in a splitter SP in  $m$  channel signal parts which are supplied to enhancing means EM. The remaining  $n-m$  channel signal parts are supplied  
30 directly to a combiner COM.

In the enhancing means EM comprising in this example  $EM_1$ - $EM_m$  the  $m$  channel signal parts are processed with a transfer function which is preferably monotone and which is anti-symmetric ( $f(-x) = -f(x)$ ).

After processing in the enhancing means the  $m$  channel signal parts are supplied to the combiner COM to be combined with the  $n-m$  channel signal parts. The combiner supplies an  $l$  channel signal to  $l$  loudspeakers  $L_1 - L_l$ .

5

Any anti-symmetrical preferably monotonous function  $f(-x) = -f(x)$  can be used for the transfer function of the surround sound processing unit, for example:

$$y(x) = c_1 \tanh(c_2 x).$$

10 The value  $c_1$  determines the maximum end level of the function  $y$ . The value  $c_2$  will be chosen such that the monotone decreasing slope of the function is in the necessary amplitude range.

It is also possible that the user is given the possibility to choose the constant values  $c_1$  and  $c_2$ . Further it is possible that the constant value  $c_1$  and  $c_2$  can be made  
15 depending on the input signal.

Typical values of  $c_1$  and  $c_2$  could be as an example with  $|x|_{\max} = 2^{15}$  (16 bits including the sign bit),  $c_1 = 7824$  and  $c_2 = 25000$ . For small  $x$  :  $y/x$  is approximately  $c_2/c_1 = 3.2$  or approximately equal to 10dB gain.

20 Figure 2 shows an example of a transfer function of the enhancing means  $EM_2$  for use in an audio-reproducing device according to the invention.

The enhancing means comprise in this example a non-linear device which has a transfer function with the above described form.

25 The man skilled in the art will be well aware of a lot of amendments of the examples of the device according to the invention, which will fall within the scope of the present invention.

For example each channel part can be handled with a separate transfer function  
30 with separate coefficients or with different coefficients for each channel.

The enhancing means EM can for example obtain the transfer function in the analog domain by using a so called long tail pair whereby a current is taken over from one transistor to the other transistor having a  $\tanh(x)$  transfer function.

Further it is also possible to obtain the enhancing means in the digital domain by using either a table and using (spline) interpolation or also a  $\tanh(x)$  function.

The above-described invention can be used by all kinds of multi channel  
5 signals. For example this invention can be used together with surround sound signals.

Further the values  $c_1$  and  $c_2$  can be equal for each channel or can also be chosen for each channel independently. Also is it possible that the values are determined on the basis of the received input signal.

EPO - DG 1

5

15.12.2000

18. 12. 2000

CLAIMS:

(100)

1. Audio reproducing device comprising an input for receiving an  $k$ -channel input signal, an output for supplying an  $l$ -channel output signal to  $l$  loudspeakers, an audio processing unit for processing the input signal, which audio processing unit comprises enhancing means for enhancing a  $m$ -channel signal part of the  $k$ -channel input signal,  
5 whereby  $m \leq n$  and the enhancing means have a preferably monotone transfer function.
2. Audio reproducing device according to claim 1 characterized in that the enhancing means comprise a non-linear device with a monotone transfer function, which is anti-symmetrical.  
10
3. Audio reproducing device according to claim 1 characterized in that the transfer function is  $\tanh(x)$ .
4. Method of reproducing an audio signal comprising a step of processing a received input signal, supplying separated signal parts, processing a signal part where by the  
15 processing has a transfer function with a monotone decreasing slope.
5. Method as claimed in claim 1 characterized in that the transfer function is  $\tanh(x)$ .

***This Page Blank (uspto)***

ABSTRACT:

EPO - DG 1

18. 12. 2000

(100)

Multi channel audio reproduction has already been used for some time. For example the so-called surround sound signals can improve the appearance of reproduced sound to a great extent.

- To improve the reproduction of sound signals even further it is in this
- 5 invention proposed to use enhancing means to process at least some signal parts even further using a monotone transfer function.

Fig. 1

***This Page Blank (uspto)***




FIG. 1




FIG. 2

**This Page Blank (uspto)**